

Shearing Machine

Machine Code	Shearing Length	Nominal Rake Angle (MS)	Maximum Rake Angle (MS)	Nominal Rake Angle (SS)	Maximum Rake Angle (SS)	Rake Angle	Rake Angle Range	Stroke/Minute at Min. & Max. Rake Angle	Hold Downs	Holding Force (Kgs)	Power (HP)	Packing Dimension (LxWxH) (mm)	Approx Weight (Kgs.)
IP HVR - 225	2500	2	3.15	1	1.6	1°	0.5-2°	22-10	13	1800	3	2900 X 1600 X 1500	2500
IP HVR -230	3000	2	3.15	1	1.6	1°	0.5-2°	18-8	15	1800	3	3400 X1600 X1500	2800
IP HVR -315	1500	3.15	4	2	3	1° 15'	0.5-2°	24-10	8	2000	5	2250 X1850 X2050	2000
IP HVR - 325	2500	3.15	4	2	3	1° 15'	0.5-2°	28-13	13	2500	5	3200 X1850 X1950	3500
IP HVR - 330	3000	3.15	4	2	3	1° 15'	0.5-2°	24-9	15	2500	5	3700 X1850 X1950	4000
IP HVR - 415	1500	4	6	3	4	1° 37'	0.5-3°	24-10	8	4500	5	2250 X1850 X2050	3200
IP HVR - 420	2000	4	6	3	4	1° 37'	0.5-3°	24-10	11	6200	7.5	2750 X1850 X2050	3500
IP HVR -425	2500	4	6	3	4	1° 37'	0.5-3°	22-8	13	8000	7.5	3300 X2250 X2400	5000
IP HVR - 430	3000	4	6	3	4	1° 37'	0.5-3°	22-8	15	10000	10	3700 X2250 X2400	6000
IP HVR - 440	4000	4	6	3	4	1° 45'	0.5-3°	18-6	20	12000	10	4500 X2250 X 2400	8100
IP HVR - 615	1500	6	8	4	6	1° 45'	0.5-3°	24-8	8	6500	10	2250 X 1900 X2100	4000
IP HVR - 620	2000	6	8	4	6	1° 45'	0.5-3°	22-7	11	65000	10	2750 X1900 X 2100	4300
IP HVR - 625	2500	6	8	4	6	1° 45'	0.5-3°	28-8	13	8500	15	3300 X 2250 X2500	6000
IP HVR - 630	3000	6	8	4	6	1° 45'	0.5-3°	24-6	15	10800	15	3800 X 2250 X2500	6500
IP HVR - 640	4000	6	8	4	6	2°	0.5-3°	24-6	20	13600	20	4800 X2250 X2500	8200
IP HVR - 815	1500	8	10	6	8	2°	0.5-3°	22-10	8	10500	15	2250 X2050 X2200	5200
IP HVR - 820	2000	8	10	6	8	2°	0.5-3°	18-8	11	12000	15	2750 X 2050 X2200	6000
IP HVR - 825	2500	8	10	6	8	2°	0.5-3°	24-8	13	16500	20	3300 X 2350 X2600	7500
IP HVR - 830	3000	8	10	6	8	2°	0.5-3°	20-6	15	18500	20	3800 X2350 X2600	9000
IP HVR - 840	4000	8	10	6	8	2°	0.5-3°	20-8	20	23000	25	4800 X 2350 X2600	12500
IP HVR - 1015	1500	10	13	8	10	2°	0.5-3°	20-10	8	10500	15	2250 X2050 X 2300	6000
IP HVR -1020	2000	10	13	8	10	2°	0.5-3°	18-0	11	13000	15	2750 X 2050 X 2300	7000
IP HVR - 1025	2500	10	13	8	10	2°	0.5-3°	24-8	13	17500	20	3300 X2500 X2800	9000
IP HVR - 1030	3000	10	13	8	10	2°	0.5-3°	20-6	15	20000	20	3800 X 2500 X2800	11500
IP .HVR - 1040	4000	10	13	8	10	2°	0.5-3°	18-6	20	25000	30	4800 X2500 X 2800	15000
IP HVR - 1320	2000	13	16	10	13	2°	0.5-3°	13-5	11	16500	20	2750 X 2200 X2500	7000
IP HVR - 1325	2500	13	16	10	13	2°	0.5-3°	15-10	13	32000	25	3350 X 2600 X2800	9000
IP HVR - 1330	3000	13	16	10	13	2°	0.5-3°	12-6	15	37000	25	3800 X2600 X2800	12000
IP HVR - 1340	4000	13	16	10	13	2°	0.5-3°	10-4	20	22000	30	4850 X2200 X2800	15500
IP HVR - 1620	2000	16	20	13	16	2°	0.5-3°	13-7	11	22000	25	2750 X2200 X2600	12000
IP HVR - 1625	2500	16	20	13	16	2°	0.5-3°	15-8	13	40000	30	3500 X2600 X 2900	15000
IP HVR - 1630	3000	16	20	13	16	2°	0.5-3°	12-6	15	43500	30	4000 X2600 X2900	17000
IP HVR - 1640	4000	16	20	13	16	2°	0.5-3°	10-4	20	30000	30	5100 X 2750 X2900	20000
IP HVR - 2020	2000	20	25	16	20	2°	0.5-3°	16-8	11	32000	40	2900 X 2500 X2600	17000
IP HVR - 2025	2500	20	25	16	20	2°	0.5-3°	15-8	13	48000	40	3500 X 2750 X3000	18000
IP HVR - 2030	3000	20	25	16	20	2°	0.5-3°	12-6	15	52000	40	4000 X 2750 X3000	20000
IP HVR - 2040	4000	20	25	16	20	2°	0.5-3°	10-4	20	30000	50	5100 X 2800 X3000	24000